



Mike Termondt

Ph: 1 805-649 1384 Fax: 1 805 500 4328

Mike@satcom-services.com

www.SATCOM-Services.com

GLOBALSTAR SATELLITE ANTENNAS

20M EARTH STATION ANTENNAS



- * Meets CCIR 580 and INTELSAT Requirements
- * CP/LP switchable feed
- * High RF performance
- * Galvanized steel hardware
- * Step-track control system
- * Different frequency ranges from many feed configurations
- * Antenna reflector be pre-assembly in works, special designed taper-pin easy installation and ensure on site assembly accuracy.

Antenna Accessory

- * Motorization Kits
- * Limit Switches
- * ODU Support Kits
- * Factory Feed System Testing and Documentation
- * Ocean Transport Packing
- * Foundation Kit
- * Lightning Rod Kit
- * Grounding Kit Cable-Mounting Kit
- * Anti-icing and Deicing

Options

- * L,S,X bands and multi-bands
- * 800MHz band with is available
- * Full motion antenna
- * Feed blower or deicing with automatic controls
- * Two or four Tx/Rx port in linear or circular polarized feeds

20M ANTENNA WITH 4 PORT DUAL LINER/CIRCULAR POL.FEED

	C-BAND		Ku-BAND	
	Receive	Transmit	Receive	Transmit
Operating Frequency, GHz	3.4 ~ 4.2	5.85 ~ 6.65	10.95 ~ 12.75	13.75 ~ 14.5
Antenna Gain, dBi: Tx(at Tx port to feed) Rx((at Rx port of feed)	60.20+20lg [f/6(GHz)] 56.75+20lg [f/4(GHz)]		66+20lg [f/11.8(GHz)] 67.17+20lg [f/14(GHz)]	
Cross Polarization Isolation for LP	On Axis: 35dB, Within 1dB beamwidth:30dB			
Axial Ratio (dB) for CP	0.5dB per port			
VSWR	CP:1.25:1		LP:1.3:1	
Antenna Noise Temperature:	2 port feed		2 port feed	
5° Elevation	54°K		68°K	
10° Elevation	46°K		60°K	
20° Elevation	36°K		52°K	
40° Elevation	30°K		44°K	
-3dB Beam Width, Mid-band	0.24°	0.16°	0.083°	0.073°
Total Power Handling Capability	5kw (cw) per Tx port			
Feed Interface	CPR-229G	CPR-137G	WR-75	WR-75
Feed Insertion Loss	0.4	0.4	0.5	0.5
Port to Port Isolation: Tx to Rx(Tx Freq) Rx to Rx Tx to Tx(Same Band)	85dB CP: 20dB LP: 30dB CP: 20dB LP: 30dB			
Radiation Pattern:First Sidelobe	≤-14, Meet ITU-RS.580-5 specifications			

MECHANICAL SPECIFICATION

Antenna Pointing Range Azimuth Elevation	0° ~ 170°/ 0° ~ 360°(Continuous) 0° ~ 90°(Continuous)
Finishes Reflector Surface Pedestal & Back Structure	Aluminum panels with high-diffusing white paint Galvanized steel
Surface Accuracy (RMS)	0.7mm (R.M.S)

ENVIRONMENTAL SPECIFICATION

Operational Wind	72km/h Gusting to 100km/h
Survival Wind	200km/h
Rain	Up to 100mm/h operational and survival
Relative Humidity	Up to 100% operational and survival
Temperature	-40°C ~ + 60°C
Radial Ice(Survival)	25mm on all surface
Shock and Vibration	As encountered during shipment by commercial air, sea, or truck
Corrosive atmosphere	As encountered in coastal regions and/or heavily industrialized areas
Seismic (Survival)	0.3g (H), 0.15g (V)