



## **ASC300 Series Beacon Receiver Ethernet Specifications**

### **Ethernet Interface**

Number of Ports 1  
Speed 10/100 Mbps, auto MDI/MDIX  
Connector (s) 8-pin RJ45  
Magnetic Isolation Protection 1.5 KV built-in

### **Serial Communication Parameters**

Data Bits 5, 6, 7, 8  
Stop Bits 1, 1.5, 2  
Parity None, Even, Odd, Space, Mark  
Flow Control RTS/CTS and DTR/DSR, XON/XOFF  
Baud Rate 110 bps to 230.4 Kbp

### **Software**

Network Protocols ICMP, IP, TCP, UDP, DHCP, BOOTP, Telnet, DNS, SNMP, HTTP, SMTP

### **Configuration Options**

Web Console, Serial Console, Telnet Console,  
Windows Utility Windows Real COM  
Windows 7/2008/Vista/2003/XP x86/x64 Windows 2000/NT/ME/98/95 XP  
Embedded Embedded CE 5.0/6.0

### **Fixed TTY Drivers**

SCO Unix, SCO OpenServer, UnixWare 7, UnixWare 2.1, SVR 4.2, QNX 4.25, QNX 6, Solaris 10, FreeBSD, AIX 5.x, HP-UX 11i

### **Environmental Limits**

Operating Temperature 0 to 55°C (32 to 131°F)  
Storage Temperature -40 to 85°C (-40 to 185°F)  
Ambient Relative Humidity 5 to 95% (non-condensing)

### **Standards and Certifications**

Safety UL 60950-1, EN 60950-1  
EMC CE, FCC  
EMI EN 55022 Class A, FCC Part 15 Subpart B Class A  
EMS EN 55024

[Request A Quote](#)