

Ka-75V-KASAT

iNetVu[®]
by C-COM Satellite Systems Inc.

TECHNICAL SPECIFICATIONS

The iNetVu[®] Ka-75V-KASAT Drive-Away Antenna is a 75 cm auto-acquire satellite antenna system which can be mounted on the roof of a vehicle for Broadband Internet Access over KA-SAT Tooway services. The system works seamlessly with the iNetVu[®] 7024C Controller providing fast satellite acquisition within minutes, anytime anywhere.

"Authorized for use on KA-SAT NEWSPOTTER NEWSGATHERING service by Eutelsat"



Features

- One-Piece, high surface accuracy, offset feed, steel reflector
- Heavy duty feed arm now supports both type of Transceivers: Standard Tria and new eTRIA
- Designed to work with the iNetVu[®] 7024C Controller
- Works seamlessly with the world's emerging commercial KA-SAT satellite Surfbeam II/PRO Auto-acquire modems
- Auto beam select on KA-SAT Tooway services
- 2 Axis motorization
- Supports manual control when required
- One button, auto-pointing controller acquires Ka-band satellite within 2 minutes
- Locates satellites using the most advanced satellite acquisition methods
- Supports Skyware Global 75 cm Ka antenna
- Standard 2 year warranty



Application Versatility

If you operate in Ka-band, the Ka-75V-KASAT system is easily configured to provide instant access to satellite communications for any application that requires reliable and/or remote connectivity in a rugged environment. This next generation mobile Ka terminal delivers affordable broadband Internet services (High-speed access, Video & Voice over IP, file transfer, e-mail or web browsing). Ideally suited for industries such as Oil & Gas Exploration, Military Communications, Disaster Management, SNG, Emergency Communications Backup, Cellular Backhaul and many others.

http://www.eutelsat.com/files/contributed/support/pdf/Eutelsat_Broadband_Services.pdf (p.12)
<http://www.eutelsat.com/files/contributed/products/pdf/KA-SAT-SNG-terminals.pdf>

C-COM
SATELLITE SYSTEMS INC.

Ka-75V-KASAT



by C-COM Satellite Systems Inc.

TECHNICAL SPECIFICATIONS

Mechanical

Reflector	75cm Elliptical Antenna, offset feed
Platform Geometry	Elevation over Azimuth
Deployment Sensors	GPS antenna Compass $\pm 2^\circ$ Tilt sensor $\pm 0.1^\circ$
Azimuth	Full 360° in overlapping 200° sectors
Elevation	0 - 90°
Polarization	Circular, Auto-switching
Elevation Deploy Speed	Variable, 10°/sec typ.
Azimuth Deploy Speed	Variable, 10°/sec typ.
Peaking Speed	0.1°/sec

Environmental

Survival	
Wind Deployed	160 km/h (100 mph)
Wind Stowed	225 km/h (140 mph)
Temperature	-40°C to 65°C (-40°F to 150°F)
Operational	
Wind	72 km/h (45 mph)
Temperature	-30°C to 55°C (-22°F to 130°F)

Thermal Test per MIL-STD-810F, Method 501.4/502.4, High/Low Temperatures
Vibration Test per MIL-STD-810F, Annex A, Category 4, Truck/Trailer/Tracked
Shock Test per IEC 60068-2-27, Appendix A, Water Ingress per IP-66

Electrical

Rx & Tx Cable	2 RG6 cables - 10 m (33 ft) each	
Control Cables		
Standard	10 m (33 ft) Ext. Cable	
Optional	up to 60 m (200 ft) available	
	Receive	Transmit
Frequency (GHz)	18.30 - 20.20	28.10 - 30.00
Feed Interface (Circular)	RG6	RG6
Nominal G/T	17.5 dB/K	
Nominal EIRP	48.4 dBW	

RF Interface

Radio Mounting	Feed Arm
Coaxial	RG6U from Transceiver to Base Connector

Physical

Mounting Plate	L: 131 cm (51.6") W: 45 cm (17.7")
Stowed Reflector Ext. Dims	L: 145 cm (57") W: 76 cm (29.9") H: 30 cm (11.8")
Deployed Height	122 cm (48")
Platform Weight	52 kg (115 lbs)

Motors

Electrical Interface	24VDC	8 Amp (Max.)
----------------------	-------	--------------

Shipping Weights & Dimensions*

System, with controller and standard set of cables, accessories
Crate (including Reflector, Feed/Transceiver):
185.5 cm x 112 cm x 68.5 cm (73" x 44" x 27"), 127 kg (280 lbs)
Crate (no Reflector, no Feed/Transceiver):
185.5 cm x 112 cm x 68.5 cm (73" x 44" x 27"), 118 kg (260 lbs)

*The shipping weights/dims can vary for particular shipments depending on actual system configuration, quantity, packaging materials and special requirements

Request A Quote

