# Transportable Skid



TECHNICAL SPECIFICATIONS

by C-COM Satellite Systems Inc.

The iNetVu Transportable Skid is a robust transportable base which is designed to support the iNetVu 1200 antenna system. The skid can be transported using forklifts or hoists making it possible to rapidly deploy the antenna system without the need to mount it on a trailer or a vehicle.



(Shown with the iNetVu 1200 antenna system and shock absorbers)



### Physical

Skid w/ system (without shocks) 146 cm x 205.5 cm x 66.7 cm

(57.5" x 80.9" x 26.25")

Skid w/ system (with shocks) 146 cm x 205.5 cm x 71.7 cm

(57.5" x 80.9" x 28.25")

Weight: Skid only 68.9 kg (152 lbs)

Weight: Skid w/ system 161.5 kg (356 lbs)

#### Note: (1)

The shipping weights/dims can vary for particular shipments depending on actual system configuration, quantity, packaging materials and special requirements

## Features

- Welded aluminum construction is rigid, lightweight & robust
- Easily handled by forks from pallet trucks and warehouse lift-trucks to large outdoor vehicles
- Fork access from all 4 sides
- · Easily hoistable
- Antenna can be quickly mounted/demounted
- Ships fully assembled for very fast integration and deployment
- Optional shock absorbers to greatly reduce road damage
- Extra strongpoints that accommodate a rack case and generator for self-contained antenna deployment
- Optional cable spool



## Shipping Weights & Dimensions (1)

Skid w/ system + lid: 146 cmx 205.5 cm x 83.8 cm (57.5" x 80.9" x 26.25"), 225 kg (456 lbs)

Lid: 45.4 kg (100 lbs)

Controller + Cables (30ft): 18.1 kg (40 lbs)

Total shipping weight of Skid w/ lid, system, controller + cables:

225.5 kg (496 lbs)



Request A Quote