

# Type 243: 2.4m Receive-Only Antenna System



## PRODUCT SPECIFICATIONS

Detail Photos  
(on right from top to bottom)  
Pre-assembled Az/EI Mount  
Fine-elevation adjustment with stamped degree scale  
Ku feed assembly with LNB cover



The one-piece reflector is thermoset-molded for strength and surface accuracy.



## 2.4 m Receive-Only Antenna System TYPE 243

The Skyware Global 1.8 m Type 180 Offset Antenna is a rugged commercial grade product suitable for the most demanding applications. The reflector is thermoset-molded for strength and surface accuracy. Molded into the rear of the reflector is a network of support ribs which not only strengthens the antenna, but also helps to sustain its critical parabolic shape.

The Az/EI mount is constructed from heavy-gauge steel to provide a rigid support to the reflector. The Az/EI mount secures the antenna to any 114 mm (4.50") O.D. mast and prevents slippage in high winds.

A specially formulated powder paint process offers excellent protection from weather-related corrosion

- All materials comply with EU directive No. 2002/95/EC (RoHS).
- One-piece thermoset-molded offset reflector.
- Fine azimuth and elevation adjustment.
- Galvanized 19 mm (.75") O.D. feed support legs.
- Factory pre-assembled mount.
- Plated hardware for maximum corrosion resistance.
- Available with C-band or Ku-band feeds.



Satcom solutions for the long haul

• PRODUCT SPECIFICATIONS

2.4m Receive Only Antenna System

RF Performance

	C-band	Ku-band
Effective Aperture	2.4 m (96 in)	12.4 m (96 in)
Operating Frequency	3.7 - 4.2 GHz	10.95 - 12.75 GHz
Polarization	Linear (Circular Optional)	Linear (Circular Optional)
Gain @ 3.95/11.95 GHz	38.0 dBi	47.6 dBi
3 dB Beamwidth	2.1°	0.7°
Antenna Noise Temperature @ 30° Elevation	36° K	31° K
VSWR*	1.4:1	1.3:1
Antenna Cross Polarization	30 dB on Axis (Linear)	30 dB on Axis (Linear)
Feed Interface	CPR-229	WR75 Flat Flange

(All specifications typical)

\*Function of feed specifications

Mechanical Performance

Reflector Material	Glass Fiber Reinforced Polyester
Antenna Optics	One-Piece Offset Feed Prime Focus
Mount Type	Elevation over Azimuth
Elevation Adjustment Range	10° - 90° Continuous Fine Adjustment
Azimuth Adjustment Range	360° Continuous ± 12° Fine Adjustment
Mast Pipe Interface	168 mm (6.63 in) Diameter
Wind Loading	Operational .80 km/h (50 mph) Survival 200 km/h (125 mph)
Temperature	-50°C to 80°C
Humidity	0 to 100% (Condensing)
Atmosphere	Standard Hardware Meets 500 Hour Salt Spray Test Requirements (ASTM B-117)
Solar Radiation	360 BTU/h/ft <sup>2</sup>
Shock and Vibration	As Encountered During Shipping and Handling



Satcom solutions for the long haul



REV 03/15-02  
Page 2 of 2

Request A Quote