



The IBUC Advantage

All IBUCs are equipped with cutting-edge intelligent technology:

- Highest quality & exacting performance guaranteed through individual unit testing over temperature
- Superior linearity for maximum useable output power
- Amplifier overdrive protection
- User-selectable AGC/ALC for optimal performance & compatibility with modem adaptive coding
- New high capacity microprocessor & extended M&C functions

ULTIMATE MANAGEMENT & CONTROL

- » Local Web Interface & NMS-Friendly SNMP «
- » 70+ User Configurable Thresholds & Alarms «
- » Upgraded Event Log with 1,000 Sensor Readings «
- » Performance Trend Analysis Tools & Statistical logs «
- » Embedded Web Pages for Universal Web Browser Access «

C-Band IBUC 2

Smaller, lighter models with RJ45 interface.



5W
to
80W

GaAs
Tech
Amplifier

3
Year
Warranty

Applications

The **IBUC 2** is a compact integrated BUC/GaAs SSPA designed for higher performance & reliability. Block Upconverters based on linear GaAs amplifier technology require minimal output power backoff. 24-48-hour environmental chamber testing guarantees $P_{1\text{dB}}$ output power over frequency and temperature range.

Multiple sensors & a new, high-capacity microprocessor provide tools to optimize terminal performance. The **IBUC 2** is a popular choice for medium-high power Satcom terminals in telecom, defense, air traffic control, government & other demanding network applications.

Options

- 1+1 Transmit Redundancy
- High Stability Internal 10 MHz Reference with Auto-Detection
- Several Factory Select Bands
- AC or DC Input Models
- Mounting Brackets
- Optional Type N or F-Type Input Connectors
- Waveguide or Type N Output
- Handheld Terminal

C-Band IBUC 2

Frequency Range	RF (MHz)	IF (MHz)	
		Inverting	Non-Inverting
Sense			
Band 1 Std C	5850 to 6425	950 to 1525	950 to 1525
Band 2 Palapa	6425 to 6725	975 to 1275	1125 to 1425
Band 3 INSAT	6725 to 7025	1150 to 1450	965 to 1265
Band 4 Ext C	5850 to 6650	950 to 1750	950 to 1750
Band 5 Full C	5850 to 6725	975 to 1850	950 to 1825

Input

VSWR/ Impedance	1.5:1 / 50 Ohm
Input Connector	Type N Female (50 Ohm)
Input Connector Options	Type F (75 Ohm), TNC (50 Ohm)
Input Power Detector Range	-55 to -20 dBm

Gain

Small Signal Gain (L-band to RF) with attenuator set to 0 dB

Power	Gain
5W	68 dB min
10W	71 dB min
15W	72.8 dB min
20W	74 dB min
25W	75 dB min
30W	75.8 dB min
40W	77 dB min
50W	78 dB min
60W	79 dB min
80W	80 dB min

Attenuator Range	30 dB variable in 0.1 dB steps	
Gain Flatness	Bands 1/2/3	Bands 4/5
	3 dB p-p max	4 dB p-p max
Full Band	36 MHz	1 MHz
	1 dB p-p max	0.25 dB p-p max
	0.25 dB p-p max	0.25 dB p-p max

Gain Variation Over Temperature		
Open Loop	3 dB p-p max	4 dB p-p max
With AGC	1 dB p-p max	1 dB p-p max

RF Output

Interface	CPR-137G or N(f)
VSWR	1.5:1 max

Rated Output Power

Power	P _{1dB}
5W	+37 dBm min
10W	+40 dBm min
15W	+41.8 dBm min
20W	+43 dBm min
25W	+44 dBm min
30W	+44.8 dBm min
40W	+46 dBm min
50W	+47 dBm min
60W	+47.8 dBm min
80W	+49 dBm min

Note: For 40W & Above, Output Power in Bands 4 & 5 is Reduced by 0.5 dB.

IMD3 (2 Carriers, 3 dB TOBO)	-26 dBc max
Level Stability with ALC	± 0.5 dB
Output Power Detector Range	Rated Power to -20 dB
Power Reading Accuracy	± 1.0 max
Spurious	
	In Band -65 dBc
	Out Band Complies with EN 301 443 & MIL STD 188-164B.
Harmonics	-50 dBc max
Output Noise Power Density	
	TX <- 78 dBm/Hz
	RX <- 145 dBm/Hz

SSB Phase Noise

Offset	External Reference	IBUC 2
10 Hz	-115 dBc/Hz	-54 dBc/Hz
100 Hz	-140 dBc/Hz	-79 dBc/Hz
1 KHz	-150 dBc/Hz	-89 dBc/Hz
10 KHz	-155 dBc/Hz	-94 dBc/Hz
100 KHz	N/A	-100 dBc/Hz
1 MHz	N/A	-110 dBc/Hz

External Reference (Multiplexed on TX IFL)

Frequency & Level	10 MHz	-12 to +5 dBm
-------------------	--------	---------------

Internal Reference- Optional

Local Oscillator Frequency

Band	Sense	Inverting	Non-Inverting
Band 1		7375 MHz	4900 MHz
Band 2		7700 MHz	5300 MHz
Band 3		8175 MHz	5760 MHz
Band 4		7600 MHz	4900 MHz
Band 5		7700 MHz	4900 MHz

IBUC Power Supply

Voltage	DC	48 ± 11 VDC
	AC	100 to 240 VAC

Options for 5W, 10W 24 ± 4 VDC

DC via coax available on 5W-25W

Power Consumption	DC	AC
5W	60W	75 VA
10W	85W	120 VA
15W	125W	150 VA
20W	154W	200 VA
25W	168W	210 VA
30W	188W	220 VA
40W	300W	330 VA
50W	320W	350 VA
60W	360W	400 VA
80W	N/A	540 VA

Monitor & Control

Ethernet (HTTP, Telnet, SNMPv2e) via RJ45 Connector

RS232/485, Handheld Terminal via MS-Type Connector, FSK multiplexed on TX IFL.

Environmental

	5W-50W	60W/80W
Operating Temperature	-40°C to +60°C	-40°C to +55°C
Relative Humidity	100% Condensing	
Altitude	10,000 ft (3,000 m) ASL	

Mechanical

	DC Powered	AC Powered
5W-10W	10.5 x 6 x 3.8 in. 267 x 152 x 97 mm	10.5 x 6 x 4.2 in. 267 x 152 x 107 mm
	9.3 lbs (4.2 kgs)	10.5 lbs (4.8 kgs)
15W-30W	10.5 x 6 x 5.2 in. 267 x 152 x 132 mm	10.5 x 6 x 5.6 in. 267 x 152 x 142 mm
	10.8 lbs (4.9 kgs)	11.7 lbs (5.3 kgs)
40W-80W	10.5 x 6 x 5.7 in. 267 x 152 x 145 mm	10.5 x 6 x 6.1 in. 267 x 152 x 155 mm
	11.5 lbs (5.2 kgs)	12.4 lbs (5.6 kgs)

Specifications subject to change without notice.

Updated 11/30/2020