



C-Band **IBUC G**

400W GaN IBUC



400W P_{Lin} 250W

GaN
Tech
Amplifier

3
Year
Warranty

The IBUC Advantage

All IBUCs are equipped with cutting-edge intelligent technology:

- Highest quality & exacting performance guaranteed through individual unit testing over temperature
- Superior linearity for maximum useable output power
- Amplifier overdrive protection
- User-selectable AGC/ALC for optimal performance & compatibility with modem adaptive coding
- New high capacity microprocessor & extended M&C functions

ULTIMATE MANAGEMENT & CONTROL

- » Local Web Interface & NMS-Friendly SNMP «
- » 70+ User Configurable Thresholds & Alarms «
- » Upgraded Event Log with 1,000 Sensor Readings «
- » Performance Trend Analysis Tools & Statistical logs «
- » Embedded Web Pages for Universal Web Browser Access «

Applications

The **IBUC G** delivers the highest available output power, making it an ideal solution for high data rate applications such as maritime, broadcast and network hubs. The 400W model produces +54 dBm of linear output power.

Gallium Nitride amplifier technology enables smaller packaging for antenna mounting, eliminating the losses in long waveguide runs. And the greater power efficiency translates to an appreciable reduction in power consumption. Comparing favorably with earlier technology TWTAs, the GaN **IBUC G** delivers maximum linear output power with the reliability of solid state.

Options

- 1+1 Transmit Redundancy with Eco-Mode
- High Stability Internal 10 MHz Reference with Auto-Detection
- Several Factory Select Bands
- Mounting Brackets
- Type N or F-Type Input Connectors
- Handheld Terminal

C-Band IBUC G

Frequency Range	RF (MHz)	IF (MHz)	
Sense		Inverting	Non-Inverting
Band 1 Std C	5850 to 6425	950 to 1525	950 to 1525
Band 2 Palapa	6425 to 6725	975 to 1275	1125 to 1425
Band 3 INSAT	6725 to 7025	1150 to 1450	965 to 1265
Band 4 Ext C	5850 to 6650	950 to 1750	950 to 1750
Band 5 Full C	5850 to 6725	975 to 1850	950 to 1825

Input

VSWR/ Impedance	1.5:1 / 50 Ohm
Input Connector	Type N Female (50 Ohm)
Input Connector Options	Type F (75 Ohm), TNC (50 Ohm)
Input Power Detector Range	-50 to -15 dBm

Gain

Small Signal Gain (L-band to RF) with attenuator set to 0 dB 82 dB min

Attenuator Range 30 dB variable in 0.1 dB steps

Gain Flatness	
Full Band	4 dB p-p max
36 MHz	1.5 dB p-p max
1 MHz	0.25 dB p-p

Gain Variation Over Temperature	Bands 1/2/3	Bands 4/5
Open Loop	3 dB p-p max	4 dB p-p max
With AGC	1 dB p-p max	1 dB p-p max

RF Output

Interface	CPR-137G
VSWR	1.3:1 max

Output Power

	400W	
	Band 1	Bands 2/3/4/5
at P _{sat} (typ)	+56 dBm	+55.5 dBm
at P _{lin} (min)	+54 dBm	+53.5 dBm

P_{lin} is the maximum linear power as defined by MIL STD 188-164B

Level stability with ALC	± 0.5 dB
Output power detector range	Rated power to -20 dB
Power reading accuracy	± 1.0 dB max.

Spurious @P _{lin}	
In Band	-70 dBc
Out of Band	Complies with EN 301 443 & MIL-STD 188-164B

Harmonics @ P_{lin} -50 dBc max.

Output Noise Power Density	
Tx	< - 76 dBm/Hz
Rx	< - 145 dBm/Hz

SSB Phase Noise	External Reference	IBUC G
10 Hz	-115 dBc/Hz	-54 dBc/Hz
100 Hz	-140 dBc/Hz	-79 dBc/Hz
1 KHz	-150 dBc/Hz	-89 dBc/Hz
10 KHz	-155 dBc/Hz	-94 dBc/Hz
100 KHz	N/A	-100 dBc/Hz
1 MHz	N/A	-110 dBc/Hz

External Reference (Multiplexed on TX IFL)

Frequency & Level	10 MHz	-12 to +5 dBm
Internal Reference- Optional		

Local Oscillator Frequency

Sense	Inverting	Non-Inverting
Band 1	7375 MHz	4900 MHz
Band 2	7700 MHz	5300 MHz
Band 3	8175 MHz	5760 MHz
Band 4	7600 MHz	4900 MHz
Band 5	7700 MHz	4900 MHz

IBUC Power Supply

Voltage	200 to 240 VAC	
Power Consumption	400W	
	Band 1	Bands 2/3/4/5
at P _{lin}	1850 VA	1800 VA
at P _{sat}	2150 VA	2100 VA

Monitor & Control

Ethernet (HTTP, Telnet, SNMPv2c) via RJ45 Connector

RS232/485, Handheld Terminal via MS-Type Connector

FSK multiplexed on TX IFL

Environmental

Operating Temperature	-40°C to +55°C
Relative Humidity	100% Condensing
Altitude	10,000 ft (3,000 m) ASL

Mechanical

Size	24 x 10 x 7.4 x in. 610 x 254 x 188 mm
Weight	40 lbs 18 kg

Specifications subject to change without notice.

Updated 11/30/2020