



C-Band Synthesized Frequency Up-Converter



Single
FCS101

Standard Features

- **Built-in instrumentation RMS output detector**
- **Adjustable output power threshold alarms**
- Outperforms IESS 308/309 phase noise by 5dB
- Superior linearity
- 125 kHz step size
- 40dB attenuation control range
- On-site reference aging correction capability
- Intuitive front panel user interface
- RS232 terminal and RS485 packet mode remote interface
- 10 operating gain and frequency

Overview

Converters from FCS101 series are packaged in a compact standard 1RU enclosure.

Their built-in instrumentation detector associated with discrete power thresholds alarms allows evolved system monitoring configurations. The straightforward front panel operation, and RS232 terminal mode enables quick on-site setup

Offered remote management interfaces ensure complete flexibility of integration into existing or new installations. The user-friendly front panel or the RS485 remote interface will provide full set-up and fault monitoring facilities Ethernet option will allow the operator to pilot system operation either through SNMP or Web based interface.

Delivered spectral purity, low phase noise and stability exceed the requirements of all major international satellite network operators.

The system reference guaranteeing conversion function's accuracy can optionally be provided externally, internally as a highly stable temperature compensated oscillator, or with auto-detection capacity that will use internal reference only in the absence of an externally provided one.

Application

The FCS101 range of converters operates in VSAT, SCPC Networks, DSNG/SNG, DVB-RCS and Hub systems. This makes them an ideal choice for large earth stations requiring cost effective solutions while maintaining equipment configuration flexibility. The lightweight and compact design makes the FCB100 converter as an ideal solution for mobile truck or flyaway DSNG systems. Its rugged construction can even meet the demands of military installations. The FCB100 range of converters provides an industry leading MTBF of over 120,000 hours.

Operating Bands

Model Number	RF Output	IF Frequency
ARUN-70CS-A	5.850 - 6.425 GHz	70 MHz (36 MHz BW)
ARUN-70CX-A	5.850 - 6.725 GHz	
ARUN-140CS-A	5.850 - 6.425 GHz	70 MHz (36 MHz BW)
ARUN-140CX-A	5.850 - 6.725 GHz	

Options

- 1kHz step size
- 30dB maximum gain
- 75 ohms IF impedance
- Group Delay equalization
- Ethernet port with SNMP and Web interface
- Autosensing Internal /External Reference
- Input Monitor and Output Monitor
- 1:1 Redundant Ready
- 1:N Redundant Ready

Redundancy

The FCS-100 converter series redundancy options allow their incorporation in redundant system from 1:1 up to 1:12. 1:1 redundancy is performed with an additional redundancy shelf for a system size of 3RU. Higher order redundancy operates through a redundancy controller shelf with the extra benefit of a single bus for complete system M&C. Given each Switch Panel can handle up to four (4) converter units; a complete 1:12 system requires a space of 17U.

Associated documents

- 1:N Switch Controller for Frequency Converters
- 1:1 Redundancy for Frequency Converters.



C-Band Synthesized Frequency Up-Converter

Technical Specifications							
Up-Converter							
IF Input							
Impedance	50 Ω (75 Ω *)						
Input Connector	BNC (female)						
Return loss	18 dB						
Input monitor coupling*	20dB +/- 1dB						
Input monitor connector*	BNC (female)						
RF Output							
Output level	0 dBm at P1dB						
IMD3 (two tone)	-40 dBc max @ -10 dBm output						
Output connector	Type N (female)						
Connector Impedance	50 Ω						
Return loss	18 dB						
Output monitor coupling*	24 +/- 1dB						
Output monitor connector*	SMA (female)						
Power detection range	-25 to +11 dBm, +/-1 dB						
Transfer Characteristics							
Frequency range	(See table on front page)						
Conversion Gain	20 dB (30dB option)						
Gain adjustment	40 dB (0.1 dB step size)						
Gain flatness	1.2 dB p-p max. 36 MHz 1.8 dB p-p max. 72 MHz						
Gain stability	± 0.25 dB max. /24 hours ± 1 dB over temp. range						
Spurious	< -55 dBc related @ -10 dBm output < -60 dBm non-related						
Group delay	8 ns p-p typical						
Group delay equalization*	36MHz	Linear	0.03 ns/MHz	Parabolic	0.01 ns/MHz ²	Ripple	1 ns p-p
	72MHz	Linear	0.025 ns/MHz	Parabolic	0.003 ns/MHz ²	Ripple	1 ns p-p
Phase noise (dBc/Hz)	100Hz		1kHz		10kHz		100kHz
	-65		-75		-85		-100
Synthesizer step size	125k kHz (1kHz option)						
Reference			Mechanical				
External Reference	10 MHz, +/- 5 dBm input level		Dimensions	Width 19" (482.6 mm)			
Internal reference stability	$\pm 2 \times 10^{-8}$ over 0°C to +50°C			Height 1U 1.75" (44.5 mm)			
Aging	$\pm 2 \times 10^{-10}$ / day $\pm 5 \times 10^{-8}$ / year			Depth 22" (558.8 mm)			
Environmental			Power Supply				
Operational	0°C to +50°C standard		Voltage	90 – 265 VAC (47 – 63 Hz)			
Storage	-55°C to +85°C		Power	40W (typical, single converter)			
Humidity	Non-condensing		Connector	IEC 603320 10A			
Altitude	3,000m AMSL						
			Monitor and Control				
			RS 485	DB9			
			RS 232	DB9			
			Discrete	DB9			
			Ethernet *	RJ45 F			

Request A Quote