



# ALB130 Lite Series

Lite 40W  
Ku-Band Block-Up Converter

This small and light weight new Ku-Band BUC is ideal for SOTM applications and also benefits fixed and maritime applications.

Designed to be mounted on the feed horn, the BUC has low power consumption with less than 280W. The unit works on a wide range DC power supply of 38V to 60V. Innovation and efficient thermal design makes the BUC one of the smallest, robust, reliable and rugged enough to withstand outdoor conditions in the industry.

The unit can be configured to work in 1:1 redundant mode by adding on a simple redundancy option to the basic unit.

## Features

- Compact and lightweight
- Feed mountable
- Available in both standard and extended Ku-Band
- Forward power detection facility
- Intuitive monitoring & control through RS232/485 & Ethernet (SNMP & HTTP)
- Auto ranging 38 to 60VDC Power Supply
- Optional input AC voltage
- Automatic fault identification & alarm generation
- IP65 rated housing (Weather proof Construction)
- Wide operating temperature range -40°C to +60°C
- RoHS compliant
- Built-in RRF filter

## Quality Assurance

100% of all BUCs go through stringent quality checks in addition to well defined Electrical Stress Screening to ensure operation in harsh outdoor environments. The BUCs are also subjected to seal test for water ingress verification.

## Reliability

Field proven under harsh environment conditions, Agilis ODUs can withstand temperature ranging from -40°C to +60°C with up to 100% humidity.

# ALB130 Lite Series

Lite 40W

Ku-Band Block-Up Converter

## Technical Specifications

### RF Specifications

<b>Transmit Frequency</b>	14.0GHz – 14.5GHz 13.75GHz – 14.5GHz
<b>IF Frequency Range</b>	950MHz to 1450MHz 950MHz to 1700MHz
<b>L0 Frequency</b>	13.05GHz (Ku-Band) 12.8GHz (Extended Ku-Band)
<b>Output Power (P<sub>1dB</sub>)</b>	46dBm
<b>Spectral Re-growth</b>	30dBc @ 2dB backoff from P1dB at 1.0 x symbol rate offset for OQPSK or QPSK
<b>Inter Modulation</b>	-25dBc @ Relative to combine power of two carriers at 3dB total power backoff from P1dB
<b>Small Signal Gain</b>	74dB Min
<b>Gain Flatness</b>	±2dB over the O/P frequency band
<b>Gain Variation</b>	±2dB over the operating temperature range
<b>Gain Control</b>	20 dB in step of 0.5 dB
<b>O/P spurious</b>	According to EN301428
<b>Phase Noise @ Offset</b>	
<b>1KHz</b>	-73dBc/Hz
<b>10KHz</b>	-83dBc/Hz
<b>100KHz</b>	-93dBc/Hz
<b>I/P VSWR</b>	1.5:1
<b>O/P VSWR</b>	1.25:1 (with optional external isolator)
<b>Noise Power Density Tx BD</b>	70dBW/4KHz
<b>Rx BD</b>	142dBW/4KHz

### DC Power

<b>Prime Power</b>	48VDC (range 38 to 60VDC) via external MS connector Optional 230VAC (range 96 to 264VAC) with external power supply
<b>Power Consumption</b>	280W (Typical @ 46dBm)

### Interfaces

<b>IF Input Interface</b>	50 Ohms N-type Female
<b>Output Interface</b>	WR 75G

### External Reference

<b>Frequency</b>	10MHz
<b>Power</b>	-5dBm to +5dBm

**External reference phase noise requirement @ frequency offset**

<b>1KHz</b>	-150dBc/Hz
<b>10KHz</b>	-155dBc/Hz
<b>100KHz</b>	-160dBc/Hz

### Monitor And Control

<b>Monitor</b>	BUC temperature Status alarm RF output power LED status indication
<b>Control</b>	Attenuation RF output mute
<b>Interface</b>	RS232/485 & Ethernet (SNMP & HTTP) via external MS connector
<b>Tx Redundancy</b>	External RCU (optional for 1+1 redundancy system requirement)

### Environmental

<b>Operating Temperature</b>	-40°C to +60°C
<b>Humidity</b>	Up to 100% Weather protection sealed to IP65

### Mechanical

<b>Dimensions</b>	192L x 120W x 97H mm
<b>Weight</b>	2.0kg
<b>Colour</b>	White Powder Coat

### Compliance Standard

<b>IEC 609501-2nd Edition</b>	International Safety Standard for Information Technology Equipment
<b>ETSI EN 301 489-12</b>	Electromagnetic Compatibility and Radio Spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) Standard for radio equipment and services; Part 12: Specific conditions for Very Small Aperture Terminal, Satellite Interactive Earth Stations operated in the frequency ranges between 4GHz and 30GHz in the Fixed Satellite Service (FSS)
<b>ETSI EN 301 489-1</b>	Electromagnetic Compatibility and Radio Spectrum Matters (ERM); ElectroMagnetic Compatibility Standard for Radio Equipment and Services
<b>FCC Part 15 Class B</b>	Two levels of radiation and conducted emissions Limits for unintentional radiators (FCC Mark)

Note: All specifications are subject to change without notice.  
Rev. 240214

Request A Quote

Agilis