



ALB170 Series

5W ~ 16W
DBS Band Block-Up Converter

This small and light weight new DBS Band BUC is ideal for SOTM applications and also benefits fixed and maritime applications.

Designed to be mounted on the feed horn, the BUC has low power consumption with less than 200W for 16W model. The unit works on a wide range DC power supply of 38V to 60V. Innovation and efficient thermal design makes the BUC one of the smallest, robust, reliable and rugged enough to withstand outdoor conditions in the industry.

The unit can be configured to work in 1:1 redundant mode by adding on a simple redundancy option to the basic unit.

Features

- Compact and lightweight
- Feed mountable
- Forward power detection facility
- Intuitive monitoring & control through RS232/485 & Ethernet (SNMP & HTTP)
- Auto ranging 38 to 60VDC Power Supply
- Optional input AC voltage
- Automatic fault identification & alarm generation
- IP65 rated housing (Weather proof Construction)
- Wide operating temperature range -40°C to +60°C
- RoHS compliant

Quality Assurance

100% of all BUCs go through stringent quality checks in addition to well defined Electrical Stress Screening to ensure operation in harsh outdoor environments. The BUCs are also subjected to seal test for water ingress verification.

Reliability

Field proven under harsh environment conditions, Agilis ODUs can withstand temperature ranging from -40°C to +60°C with up to 100% humidity.

ALB170 Series

5W ~ 16W

DBS Band Block-Up Converter

Technical Specifications

RF Specifications

Transmit Frequency	17.4GHz – 18.1 GHz 18.1GHz – 18.4 GHz
IF Frequency Range	950MHz to 1750MHz
Output Power (P_{1dB})	37dBm (5W) / 42dBm (16W)
Small Signal Gain	70dB Min (5W) / 75dB (16W)
Gain Flatness	±2dB over the O/P frequency band
Gain Variation	±2dB over the operating temperature range
Gain Control	20 dB in step of 0.5 dB
O/P spurious	According to EN301428
Phase Noise @ Offset	
1KHz	-73dBc/Hz
10KHz	-83dBc/Hz
100KHz	-93dBc/Hz
I/P VSWR	1.5:1
O/P VSWR	1.25:1 (with optional external isolator)

DC Power

Prime Power	48VDC (range 38 to 60VDC) via external MS connector Optional 230VAC (range 96 to 264VAC with external power supply
Power Consumption	110W (5W) / 200W (16W)

Interfaces

IF Input Interface	50 Ohms N-type Female
Output Interface	WR 62G

External Reference

Frequency	10MHz
Power	-5dBm to +5dBm
External reference phase noise requirement @ frequency offset	
1KHz	-150dBc/Hz
10KHz	-155dBc/Hz
100KHz	-160dBc/Hz

Monitor And Control

Monitor	BUC temperature Status alarm RF output power LED status indication
Control	Attenuation RF output mute
Interface	RS232/485 & Ethernet (SNMP & HTTP) via external MS connector
Tx Redundancy	External RCU (optional for 1+1 redundancy system requirement)

Environmental

Operating Temperature	-40°C to +60°C
Humidity	Up to 100% Weather protection sealed to IP65

Mechanical

Dimensions	160L x 93W x 85H mm (5W) 330L x 190W x 150H mm (16W)
Weight	1.2 Kg (5W) / 8 Kg (16W)
Colour	White Powder Coat

Compliance Standard

IEC 609501-2nd Edition	International Safety Standard for Information Technology Equipment
ETSI EN 301 489-12	Electromagnetic Compatibility and Radio Spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) Standard for radio equipment and services; Part 12: Specific conditions for Very Small Aperture Terminal, Satellite Interactive Earth Stations operated in the frequency ranges between 4GHz and 30GHz in the Fixed Satellite Service (FSS)
ETSI EN 301 489-1	Electromagnetic Compatibility and Radio Spectrum Matters (ERM); ElectroMagnetic Compatibility Standard for Radio Equipment and Services
FCC Part 15 Class B	Two levels of radiation and conducted emissions Limits for unintentional radiators (FCC Mark)

Note: All specifications are subject to change without notice. Rev. 171115

Request A Quote

Agilis