



# AAV980 Series

C-Band VSAT  
Outdoor Transceiver

Agilis AAV980 Series C-Band OHT (One Housing Transceiver) is a low cost RF ODU (OutDoor Unit) transceiver for satellite communication. It is designed for voice and data application operating in different modulation formats including BPSK, QPSK, QAM and FM.

Agilis AAV980 OHT is a very compact ODU that comprises of Power Supply, Upconverter, SSPA (Solid State Power Amplifier), Down Converter and low phase noise synthesizers. It has a built-in M&C for remote and local monitoring and control. In addition, Agilis has a wide range of SSPA booster options for higher power applications.

It is suitable for SCPC (Single Channel Per Carrier) or MCPC (Multi-Channel Per Carrier), DAMA (Demand Assigned Multiple Access) and TDMA (Time Division Multiple Access) applications.

## Features

- Available for all C-Band frequencies
- Broadband data transmission
- Low cost, compact model
- Easy installation & configuration
- Built-in monitor and control
- Higher power options available
- Built-in image rejection filter
- Very stable OCXO reference oscillator
- Output power monitoring
- Electronically tuneable synthesizer
- 1.0MHz frequency step size
- Redundancy ready
- Surge protection
- 70 or 140MHz IF interface

## Enhanced Monitoring and Control

Agilis AAV980 C-OHT offers M&C via RS232/485. It features full remote M&C through Windows using PC.

These include:

- Tx/Rx level monitoring
- Temperature monitoring
- RF output ON/OFF
- Frequencies selection
- Gain control
- Automatic fault identification & alarm

## Reliability

Field proven under harsh environment conditions, Agilis ODUs can withstand temperature ranging from -40°C to +60°C with up to 100% humidity.

## Quality Assurance

All Agilis ODUs go through intensive active electrical stress screening with performance being monitored during screening. In addition, all units undergo 100% waterproof test equivalent to IP65 to ensure normal operation during tropical, cold and harsh environment.

# AAV980 Series

C-Band VSAT  
Outdoor Transceiver



## Technical Specifications

### C-Band Frequency Range (GHz)

Frequency	Transmit	Receive
Intelsat	5.850 – 6.425	3.625 – 4.200
Gorizont	5.725 – 6.275	3.400 – 3.950
Insat	6.725 – 7.025	4.500 – 4.800
ST-1/Palapa C	6.425 – 6.725	3.400 – 3.700
JCSAT	6.225 – 6.485	3.940 – 4.200

### Transmit

Power	Output @P1dB (dBm) min	Min Gain (dB)	Typ AC Power Consumption (VA)
1mW	0	28 – 33	25
2W	33	58 – 63	50
5W	37	62 – 68	70
10W	40	65 – 70	120

Input Frequency	70±18MHz (Optional 140 ±36MHz)
Output Frequency	C-Band
Frequency Step Size	1.0MHz
IF Input Power Range	-25 to -5dBm
Gain Flatness for Full BW	±2.0dB max
for 36MHz BW	±1.25dB max
Gain Adjustment	20dB @1dB steps
Gain Stability (-40°C to +60°C)	±2.0dB max
Spurious (36MHz BW)	-55dBc max
Inter Modulation	-27dBc @ Relative to combine power of two carriers at 3dB total power backoff from Rated Output power

Phase Noise	
@ 100Hz offset	-60dBc/Hz
@ 1KHz offset	-70dBc/Hz
@ 10KHz offset	-80dBc/Hz
@ 100KHz offset	-90dBc/Hz

Input / Output VSWR	1.5 : 1 max
IF Input / RF Output Interface	50Ω N-Type Female
Frequency Stability	±0.5ppb/day

### Power Supply

Input Voltage (Factory Preset)	220VAC, 110VAC or 48VDC
DC Output Voltage to LNA	+12VDC at RF IN Connector

### Compliance Standard

IEC 60950	International Safety Standard for Information Technology Equipment
ETSI EN 300 673	Electromagnetic Compatibility and Radio Spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) Standard for Very Small Aperture Terminal (VSAT)
ETSI EN 301 489-1	Electromagnetic Compatibility and Radio Spectrum Matters (ERM); Electromagnetic Compatibility Standard for Radio Equipment and Services

### Environmental

Operating Temperature	-40°C to +60°C
Relative Humidity	Up to 100%

### Low Noise Amplifier

Input Frequency	C-Band
Noise Temperature at 25°C	35°K typ
Gain	55dB typ
Gain Flatness (36MHz BW)	±0.20dB max
Input VSWR	2.5 : 1
Output VSWR	1.7 : 1
RF Input Interface	WR229/G
RF Output Interface	50Ω N-Type Female

### Receive (exclude LNA)

Input Frequency	C-Band
Output Frequency	70±18MHz (Optional 140±36MHz)
Frequency Step Size	1.0MHz
Gain	45dB min
Gain Flatness for Full BW	±3.0dB max
For 36 MHz BW	±1.25dB max
Gain Stability (-40°C to +60°C)	±3.0dB max
Spurious (36MHz BW)	-55dBc max
Intermodulation Product	-35dBc max
Phase Noise	
@ 100Hz offset	-60dBc/Hz
@ 1KHz offset	-70dBc/Hz
@ 10KHz offset	-80dBc/Hz
@ 100KHz offset	-90dBc/Hz
Input / Output VSWR	1.5 : 1 max
RF Input / IF Output Interface	50Ω N-Type Female
Frequency Stability	±0.5ppb/day
Gain Adjustment	25dB @ 1dB step

### Monitor & Control

Interface	RS232/485
Optional Interface	FSK, Ethernet IP 10/100 Base-T, SNMP
Form "C" Relay Contacts	Optional

### Mechanical

Dimensions	340L x 255W x 70H mm (1mW, 2W, 5W, 10W OHT)
Weight	7.0kg (1mW, 2W, 5W, 10W OHT)
Colour	White Powder Coat

\*Booster with 1mW driver  
Note: All specifications are subject to change without notice.  
Rev. 300112

Request A Quote

Agilis