

# AvL TECHNOLOGIES

## Model 2410 Premium SNG/Military 2.4m Auto-Acquisition Quad-Band Vehicle-Mount Antenna

### Unique Features

- 2.4m AvL Carbon Fiber Single Piece Reflector
- Optional three-piece carbon fiber reflector
- Zero Backlash AvL Cable Drive
- Compact/Rugged Pol Gear Drive
- Rotary Joint on Pol Axis with opt. Flex W/G to BUC
- "One-Button" Auto-Acquisition
- Offset, Prime Focus 0.8/fD

### Optics

### Standard Rx/Tx Feed Optional Interchangeable Rx/Tx Feeds

- 2-Port Ku-Band Precision (Standard Cross-Pol comp.)
- Optional 2-Port Ku-Band Mode-Match (enhanced off-axis Cross-pol)
- Optional 4-Port Ku-Band Precision or Mode-Match
- Optional 2- or 4-Port Ka-Band, LP or CP
- Optional 2-Port, 3-Port or 4-Port C-Band, LP or CP
- Optional 2-Port Extended C-Band (LP)
- Optional 2-Port X-Band
- Optional 2-Port C-Band Troposcatter Feed
- Motorized Worm Drive
- AvL White (optional colors available)

### Polarization Adjustment Standard Colorization



## Mechanical

|                             |  |
|-----------------------------|--|
| Az/EI Drive                 | Motorized Zero Backlash AvL Cable Drive (Patent Pending)   |
| Polarization Drive System   | Motorized Worm Gear Drive  |
| Reflector Construction      | 2.4m Single Piece AvL Carbon Fiber; Optional three-piece carbon fiber reflector with manually folding hinged wings or motorized folding hinged wings   |
| Axis Travel                 |  |
| Azimuth                     | ±200° Standard; 270° with dual waveguide to vehicle, options include dual Ku, single C + single Ku. Special dual waveguide ±200° available (rotary joints protrude into vehicle further than standard) |
| Elevation                   | 0°-90° of reflector bore sight   |
| Mechanical                  |  |
| Electrical                  | 5° to 90° Standard limits or 5° to 65° (CE Approval)   |
| Polarization                | ±95° for 2-port and 3-port Feeds; ±50° for 2-port Wideband and 4-port Feeds, 3-Port or 4-Port C-Band   |
| Az/EI Speed                 |  |
| Slewing/Deploying (typical) | 1°/second Az, 1°/second EI   |
| Peaking (typical)           | 0.2°/second  |
| Motors                      | 24 VDC Variable Speed, Constant Torque   |
| RF Interface                |  |
| HPA Mounting                | Feed Boom, Rear of Reflector or Inside Truck   |
| Axis Transition             | Twist-flex or optional rotary joints for Ku-Band; Pol rotary joint standard for C-Band   |
| Waveguide                   | Cover Flange at Interface Point  |
| Coax                        | RG59 run from feed to base plus 25 ft. (8m); Option for 50 ohm LMR-240   |
| Electrical Interface        | 25 ft. (8m) Cable with Connectors for Controller   |
| Manual/Emergency Drive      | Hand crank on Az, EI and Pol axes  |
| Time to Acquisition         | Less than 15 minutes, 8 minutes typical  |
| Weight (approximate)        | 550 lbs. (250 kg) with Ku Feed and AAQ Controller  |
| Stowed Dimensions           | 123.5 L x 96.0 W x 24.2 H in (314 L x 244 W x 62 H cm) (may vary with CFE or 3-,4-port C-band)   |

## Environmental

|  |   |
|--|---|
| Wind – Survival  | Deployed: 80 mph (128 kph); Stowed: 125 mph (201 kph)   |
| Wind - Operational                                     | 45 mph (72 kph), gusts to 60 mph (97 kph)   |
| Pointing Loss in Wind (RX):                            |   |
| 10 mph (16 kph)  | < 0.8 dB All Bands  |
| 30 mph gusting to 45 mph<br>(48 kph gusting to 72 kph) | < 2.0 dB All Bands  |
| 45 mph gusting to 60 mph<br>(72 kph gusting to 97 kph) | < 2.0 dB C-Band, X-Band, Ku-Band  |
| Temperature:   |   |
| Operational  | -22° to 125° F (-30° to 52° C)  |
| Survival   | -40° to 140° F (-40° to 60° C)  |
| Shock and Vibration                                    | Designed for transport via rough Roads, Rail, Sea and Air                                     |
| Corrosion Protection                                   | For all regions from coastal to industrial, some periodic maintenance required for appearance |
| Humidity, Rain, Blowing Sand                           | Sealed to withstand 0-100% with condensation, >4 inches/hour (102 mm/hr), blowing to 40 mph   |

# AvL TECHNOLOGIES

## Model 2410 Premium SNG/MIL 2.4m Auto-Acquisition Quad-Band Vehicle-Mount Antenna

### RF/Electrical

| Feed Type ►                                      | Std. 2-Port Mode-Matched Ku-Band            |                                      | Opt. 2-Port X-Band (Military) |                            | Opt. 2-Port Ka-Band    |                           | Opt. 2-Port C-Band                   |                   |
|--|---|--------------------------------------|-------------------------------|----------------------------|------------------------|---------------------------|--------------------------------------|-------------------|
| RF Parameter ▼                                   | Receive                                     | Transmit                             | Receive                       | Transmit                   | Receive                | Transmit                  | Receive                              | Transmit          |
| Frequency Range (GHz)                            | 10.95 - 12.75                               | 13.75 - 14.50                        | 7.25 - 7.75                   | 7.90 - 8.40                | 20.2 - 21.2            | 30.0 - 31.0               | 3.625 - 4.2                          | 5.850 - 6.425     |
| Polarization Configuration                       | Linear Orthogonal Standard, Optional Co-Pol |                                      | Circular Pol                  |                            | Circular Pol           |                           | Linear or Circular Pol               |                   |
| Gain (mid-band) (dBi) 2-Port                     | 47.0  | 48.8                                 | 43.3                          | 44.1                       | 52.1                   | 55.0                      | 38.0                                 | 41.8              |
| Beam width (Degrees) -3dB                        | 0.7   | 0.6                                  | 1.2                           | 1.1                        | 0.4                    | 0.3                       | 2.2                                  | 1.4               |
| -10dB  | 1.3   | 1.1                                  | 2.1                           | 1.9                        | 0.8                    | 0.5                       | 4.0                                  | 2.6               |
| Radiation Pattern Compliance                     | FCC §25.209, ITU-R S.580.6, IESS 208        |                                      | MIL-STD-188-164A              |                            | MIL-STD-188-164A       |                           | FCC §25.209, ITU-R S.580.6, IESS 207 |                   |
| Antenna Noise Temperature @ 20° EI               | 61° K                                       | -                                    | 59° K                         | -                          | 104° K                 | -                         | 49° K                                | -                 |
| G/T, midband, clear horizon                      | 26.5 dB/K w/ 50°K LNB                       | -                                    | -                             | -                          | 28.5 dB/K w/ 100°K LNB | -                         | 19.5 dB/K w/ 20°K LNB                | -                 |
| VSWR   | 1.30:1                                      | 1.30:1                               | 1.30:1                        | 1.30:1                     | 1.30:1                 | 1.30:1                    | 1.30:1                               | 1.30:1            |
| Power Handling Capability                        | -   | 1K watts per Port                    | -                             | 250 watts per Port         | -                      | 1K watts per Port         | -                                    | 1K watts per Port |
| Circular Axial Ratio (within pointing cone) (dB) | -   | -                                    | 1.2                           | 1.5                        | 1.5                    | 1.0                       | 2.3                                  | 1.3               |
| Cross-Polarization Isolation LP only (dB)        |   |                                      |                               |                            |                        |                           |                                      |                   |
| On Axis  | 35  | 35                                   | -                             | -                          | -                      | -                         | 35                                   | 35                |
| Off-Axis (within pointing cone)                  | 28 (standard)<br>25 (opt Mode-match)        | 30 (standard)<br>35 (opt Mode-match) | -                             | -                          | -                      | -                         | 30                                   | 30                |
| Feed Port Isolation - Tx to Rx (dB)              | 35 dB                                       | 80 dB                                | 115 dB (incl. opt. filter)    | 115 dB (incl. opt. filter) | 85 dB                  | 85 dB (incl. opt. filter) | 65 dB                                | 105 dB            |
| Satellite System Compliance                      | FCC, Intelsat                               |                                      |                               |                            |                        |                           |                                      |                   |

### Controller

| Controller ►    | AvL AAQ  |
|-----------------|--|
| Features        | AvL one button auto-acquisition of selected satellites, including peaking and optimization of cross pol. Internal movement detector and automatic stow. Optional hand-held control and separate power supply. Certified for auto-commissioning on most satellite services. |
| Size            | Embedded ACU with separate 1 Rack Unit Controller Interface Panel (CIP) power supply with LCD and keypad. 250 W and 500 W (1.6m and larger antennas) versions available.   |
| CIP Input Power | 120/240 VAC 60/50 Hz, 6/3 A Max. Power consumption is antenna size dependent: During acquisition 150 W or 300 W is typical, ~ 50 W Idle  |

### Available Options, Upgrades & Services

- Optional feeds: 2-Port Ku-Band Mode-Match (enhanced off-axis Cross-pol), 4-Port Ku-Band Precision or Mode-Match, 2- or 4-Port Ka-Band, LP or CP, 2-Port, 3-Port or 4-Port C-Band, LP or CP, 2-Port Extended C-Band (LP), 2-Port X-Band, 2-Port C-Band Troposcatter Feed
- Ku-band H/V switch
- Add BUC/HPA Mounting (NOTE: minimum elevation may be restricted by these options)
- Upgrade to Custom RF/IF I/O cabling configurations
- Custom Colorization (contact factory for available colors)
- Optional three-piece carbon fiber reflector with removable wings, manually folding hinged wings, or motorized folding hinged wings
- Add Custom Logo on Reflector Face (1- or 2-Color; per AvL Logo Policy)
- Spare Parts Kit

Request A Quote