

# inMotion

PRELIMINARY

**iNetVu**<sup>®</sup>  
by C-COM Satellite Systems Inc.

## TECHNICAL SPECIFICATIONS



### SOTM Ka Terminal

#### Features

- Ka SOTM Antenna Terminal - Operates while vehicle is moving
- Automatic satellite acquisition and tracking
- Operates in emerging Ka-band services worldwide
- Provides affordable broadband connectivity via Satellite to mobile ground platforms (Land mobile)
- Low Profile Antenna < 33 cm in height with Look angles 10°-90°
- Compliant with FCC and ITU for Mobile VSAT (FCC 25.222, 25.138 VMES)
- Affordable, Rugged and Highly Reliable
- Operational wind speed of 180 km/h or better
- Compliant with ViaSat HTS and similar Ka-band networks



#### Application Versatility

The inMotion Ka SOTM Antenna provides an "always-on" broadband connectivity directly to any vehicle. Ideally suited for SNG, First Responders, Disaster Management, Trains, Public Transportation, Oil & Gas Exploration, Mining, Construction, Mobile Offices and Emergency Services.

**C-COM**  
SATELLITE SYSTEMS INC.

### TECHNICAL SPECIFICATIONS

#### Mechanical

Platform Size	1.3m diameter
Platform Geometry	Elevation over Azimuth
Azimuth Travel	0° to 360° Continuous
Elevation Look Angle	10° to 90°
Polarization	Dual Circular (Electronic Switching)
Elevation Speed	100°/sec
Azimuth Speed	100°/sec
Acceleration Max.	200°/sec <sup>2</sup>
Acquisition Time	< 60 sec (Initial)
Re-Acquisition Time	< 20 sec (Depending on Modem)

#### Environmental

Wind loading	
Operational	180 km/h (112 mph)
Survival	250 km/h (156 mph)
Temperature	
Operational	-30° to 60° C (-22° to 140° F)
Survival	-40° to 70° C (-40° to 158° F)
Humidity	0-100% (condensing)
IP Protection	IP66 on Connectors, IP65 on Electronic Parts
Vibration	per MIL-STD-810F, Truck/Trailer/Tracked
Shock	per IEC 60068-2-27

#### Electrical

Rx & Tx Cables	2 RG6 Cables - 10 m (33 ft) each
Control Cables	10 m (33 ft)
Voltage / Power	24V DC or 120 VAC

#### Physical

Antenna Dimensions	L: 130 cm (51.2")	W: 130 cm (51.2")
	H: 33 cm (13")	
Weight	< 40 kg (88 lbs)	
Mounting	Directly on Roof or Roof Racks	

#### Ka (Circular)

Transmit Power	3 W <sup>(1)</sup> Transceiver	
Feed	2 Port XPol	
	<b>Receive</b>	<b>Transmit</b>
Frequency (GHz)	18.30 - 20.20	28.10 - 30.00
G/T	> 13.5 dB/K at 45° Elev.	
EIRP Spectral Density Pattern	Compliant with FCC 25.138, 25.222, 25.226, 25.227 for VMES	
EIRP	43 dB at 1dB Compression & 45° Elev.	

#### Shipping Weights & Dimensions\*

Platform Crate : 138cm x138cm x 52cm (54.3" x 54.3" x 20.5"); 90 kg (198.4 lbs)

\*The shipping weights/dims can vary for particular shipments depending on actual system configuration, quantity, packaging materials and special requirements



#### Notes:

<sup>(1)</sup> Configurable for higher watt radios

Request A Quote