

# Cables

# iNetVu®

by C-COM Satellite Systems Inc.

## TECHNICAL SPECIFICATIONS



Motor Cable



Sensor Cable



Splitter Cable

The iNetVu® product line offers a wide range of cables to address the needs of its resellers. The iNetVu® standard configuration includes four types of cables:

### External Motor Cable - 8 conductor cable

- 14 AWG / 16 AWG / 18 AWG
- Metalized AMP 9 Pin to AMP 9 Pin connectors
- 10m (33 feet)
- Weight: 1.1 kg (2.5 lbs)

### External Sensor Cable - 25 conductor cable

- 24 AWG
- Metalized AMP 16 Pin to DB26 connector
- 10m (33 feet)
- Weight: 1.1 kg (2.5 lbs)

### External Transmit Cable (TX) - RG6 Co-axial cable

- F-Type connectors
- 75 ohm
- 10m (33 feet)
- Weight: 0.5 kg (1 lbs)

### RX Cable Splitter - 2 to 1 Splitter

- F-Type connectors
- 75 ohm
- 10 m (33 feet)
- Weight: 0.5 kg (1 lbs)

### Modem Cable - RG6 Co-axial cable

- F-Type connectors
- 75 ohm
- 1 m (3 feet)

### Controller Cable - RG6 Co-axial cable

- F-Type connectors
- 75 ohm
- 1 m (3 feet)

**Note:** The external cables are also offered in sets of 15m (50 feet), 30m (100 feet), 45m (150 feet) and 60m (200 feet). You can also order the TX cable in 50 ohm with a N-Type connector and the RX cable with a 50 ohm and a N-Type connector.

Request A Quote

**C-COM**  
SATELLITE SYSTEMS INC.