

MP-130-MOT

iNetVu[®]

by C-COM Satellite Systems Inc.

TECHNICAL SPECIFICATIONS

The iNetVu[®] MP-130-MOT is a fully motorized, auto-acquire, 130 cm carbon fiber Manpack antenna. This robust and lightweight system will point to any programmed satellite with just the push of a button on the NEW iNetVu[®] 8050 Controller. The 8050 Controller supports DVB-S2X and is fully compatible with a list of open AMIP supported modems. C-COM's highly portable, multi-segment Manpack can be hand-carried and assembled in less than 10 minutes with no tools required.



Soft Case Solution (Standard)



8050 Controller



Features

- 130 cm 7-piece carbon fibre reflector
- 2 Case Backpack type solution
- Operates in Ku, Ka or X band
- Designed to work with the iNetVu[®] 8050 Controller
- Monitor and Control Via Front Panel display or Web Interface
- Remote access and operation via Network or WiFi Interfaces
- 2 or 3 Axis Motorization
- Supports manual control when required
- One button, auto-pointing controller acquires satellite within 1 minute
- Captive hardware / fasteners
- No tools required for assembly / disassembly
- Set-up time less than 10 minutes, one person job
- 1 Year Standard Warranty

Application Versatility

The MP-130-MOT Manpack system can be easily configured to provide quick access to satellite communications for any application that requires remote connectivity in a rugged environment. Ideally suited for applications that require a quick, simple set-up; in vertical markets such as emergency response, disaster management, public safety, broadcasting, media and more.

[Request A Quote](#)

MP-130-MOT

iNetVu®

by C-COM Satellite Systems Inc.

TECHNICAL SPECIFICATIONS

Mechanical

Reflector	130 cm segmented carbon fibre
Number of Petals	7
Platform Geometry	Elevation over Azimuth
Antenna Optics	Centre Feed
Deployment Sensors	GPS antenna Compass $\pm 5^\circ$ Tilt sensor $\pm 0.1^\circ$
Azimuth	360° Continuous
Elevation	5° - 90°
Polarization	$\pm 90^\circ$ or LHCP/RHCP
Elevation Deploy Speed	Variable, 11°/sec typ.
Azimuth Deploy Speed	Variable 11°/sec typ.
Peaking Speed	Variable $\pm 0.1^\circ$

Environmental

Wind loading	
Operational	
With Ballast/Anchors	45 km/h (28.1 mph)
Survival	
With Ballast/Anchors	72 km/h (45 mph)
Temperature	
Operational	-20° to 60° C (-4° to 140° F)
Survival	-30° to 70° C (-22° to 158° F)
IP Protection	IP66
Humidity	0-100% (non-condensing)

Case

Two Backpack Soft Case (Empty): 5.4 Kg (12.0 lbs) each
Size: 84 x 51 x 41 cm (33.0" x 20.0" x 16.0"): TBD
Weight: 2-Axis (Incl. Antenna⁽¹⁾): TBD
3-Axis (Incl. Antenna⁽¹⁾): TBD

Electrical

DC Input: 36VDC @ 6A (RMS)	
AC/DC Adapter: Universal AC Input (100-277VAC) / 36VDC	
Network Interface	RJ45 Connector and WiFi (2.4GHz)
Power Consumption:	
Idle:	12W
Operational (Max):	72W

Modem Compatibility

The DVB-S2X Tuner is an integrated part of all Manpacks. It allows the iNetVu® system the option to find the satellite with and without the use of a satellite modem. Compact and adaptable, this high performance tuner is programmable to any DVB-S or DVB-S2/ACM or DVB-S2X frequency and allows the user to pre-configure specific satellite options.

Open AMIP

HNS - HT2500 (dual IFL)	Newtec - Dialog - MDM3310/MDM 2510/3XXX
Gilat - Skyedge IIc - Capricorn 4	UHP/CEL - 100/200/240
iDirect - Evolution - iQ200/X7	SpaceBridge - U7400

Ku-Band (Linear)

Transmit Power	1 to 200 watt	
Feed	2 Port XPol	
	Receive	Transmit
Frequency (GHz)	10.70- 12.75 ⁽²⁾	13.75 - 14.50
Optional Low Ku	10.70- 11.70 ⁽²⁾	12.75 - 14.50
Feed Interface	WR75	WR75 ⁽³⁾
Midband Gain (\pm .2dBi)	41.8	43.8
Sidelobe Envelope Co-Pol (dBi)		
100 λ /D ² < θ < 7°	35-25 Log θ	
7° < θ < 9.2°	13.9	
9.2° < θ < 48°	38-25 Log θ	
48° < θ < 180°	-4 Typical	
Cross-Polarization on Axis	>35 dB	
Within 1dB Beamwidth	>30 dB	
Tx/Rx Isolation	40 dB	85 dB
VSWR	1.5:1	1.5:1
G/T	21.3dB/K	

Ka-Band (Circular)

	Receive	Transmit
Operating Frequency (GHz)	17.7 - 21.2 ⁽²⁾	27.5 - 31.0
Midband Gain (\pm .2dBi)	N/A	N/A
Polarization X-POL	LHCP/RHCP Manual	
Feed Interface	WR-42	WR-28
VSWR	<1.5:1	<1.25:1
Isolation (dB)	>55	>55
G/T	21.8dB/K	

X-Band (Circular)

	Receive	Transmit
Operating Frequency (GHz)	7.25 - 7.75 ⁽²⁾	7.90 - 8.40
Midband Gain (\pm .5dBi)	N/A	N/A
Polarization X-POL	LHCP/RHCP Manual	
Sidelobe Compliant with	DSCS Req.	
Feed Interface	WR-112	WR-112
VSWR	<1.25:1	<1.25:1
Isolation (dB)	>23	>23
G/T	16.7dB/K	

Shipping Weights & Dimensions*

TBD

* The shipping weights/dims can vary for particular shipments depending on actual system configuration, quantity, packaging materials and special requirements

Notes:

⁽¹⁾ Weight indicated includes 4W BUC, LNB and 5m(16ft) Cables

⁽²⁾ LNB PLL Type required with stability better than ± 10 KHz

⁽³⁾ Maximum BUC dims supported: 9.8 cm x 9.8 cm x 4.2 cm (3.9" x 3.9" x 1.7"); 0.5Kg(1.1lbs)
Larger BUCs must use quick disconnect flex waveguide