

Innovative Communication Solutions

WAYFARER™ WFA120KA

1.2m Ka-Band Auto Fly-Away

The Norsat WAYFARER™ commercial 1.2m fly-away antenna is a fast deploying, easy-to-use, and compact SATCOM VSAT. This antenna is an excellent choice for commercial applications in various industries.

The WAYFARER 1.2m fly-away antenna offers excellent rugged and reliable satellite links for remote enterprise, energy, emergency, and media applications.

FEATURES

- Easy and intuitive LinkControl™ Interface
- · Rugged and lightweight pedestal design
- · Lightweight and durable 8 segment carbon fiber reflector
- · Fast, simple, tool-free deployment
- · Automatic 3-axis acquisition
- · 2-case packing solution
- · Wide range of Norsat BUC and LNB configurations
- · Set up in 5 minutes



SPECIFICATIONS

ELECTRICAL

Reflector Aperture 1.2m

Reflector Material Carbon fiber

Feed Configuration Center

 Tx Frequency
 29.0 to 31.0 GHz

 Rx Frequency
 18.7 to 21.2 GHz

 Tx Gain
 46.4 dBi @ 29.0 GHz

 Rx Gain
 43.3 dBi @ 18.7 GHz

Polarization Circular

Cross Polarization (Axial Ratio) 1.5 dB Tx/Rx Isolation (Port Isolation) $Tx \ge 100 \text{ dB}$

Sidelobe First sidelobe -14 dB

 Azimuth Range
 ± 200°

 Elevation Range
 10° to 90°

 Azimuth Speed
 0.1°/s to 3°/s

 Elevation Speed
 0.1°/s to 3°/s

 Tx: WR28

eed Interface Rx: WR42

Power Supply AC110-230V 50/60Hz, rated 200W, 550W max

MECHANICAL

Ruggedized weatherproof case

Case 1 Pedestal assembly Size: 79.5 cm (L) x 51.8 cm (W) x 31 cm (H);

Weight: ≤ 32Kg

Case 2 Reflector / feed Size: 84.5 cm (L) x 62 cm (W) x 49 cm (H);

Weight: ≤ 32Kg

ENVIRONMENTAL

 Wind Load - Operational
 49 km/h

 Wind Load - Survival
 100 km/h

 Operational Temperature
 -30°C to +50°C

 Storage Temperature
 -50°C to +70°C

 Humidity
 0-95%

Ingress Protection IP 65 (antenna only)

WAYFARERWFA120KA1.2MKA-BANDAUTOFLY-AWAYANTENNA

HOW TO ORDER

WFA120KA-NA

KA: Ka-Band AC POWER PLUG

 NA = North America
 (NEMA 5/15)

 UK = United Kingdom
 (BS 1363)

 EU = Europe
 (CEE 7/7)

 IEC = IEC
 (60320 CIA)

 CN = China
 (Type I Plug)

ACCESSORY OPTIONS

BUC OPTIONS BUC BUC POWER SUPPLY BUC M & C CABLE BUC MOUNTING BRACKETS

 12W
 ELMTBKA012
 PS300-AT1(NA/UK/EU/IEC)
 CABLEM+C-AT10
 WFA120KUMT-024

 25W
 ATOMBKA025
 PS300-AT1(NA/UK/EU/IEC)
 CABLEM+C-AT10
 WFA120KUMT-024

 50W
 ATOMBKA050
 PS600-AT1(NA/UK/EU/IEC)
 CABLEM+C-AT10
 WFA120KUMT-024

LNB OPTIONS SERIES

LNB 9000 Series

IFL CABLE OPTIONS NN-FF NN-NN FN-FF

MODEM CABLE OPTION (For iDirect product only)

MOD-CABLE

INTEGRATION

WF-INT Assembly, function verification, and pointing test (standard product/RF packages only)