

2021 Agilis

2.0 Meter Carbon Fiber Flyaway Antenna



The Sat-Lite Technologies Model 2021 Agilis carbon fiber flyaway antenna offers superior performance in a lightweight, portable package. This antenna features a 7 piece carbon fiber segmented reflector designed to provide high gain and low cross pol characteristics. The custom-designed elevation-over-azimuth tripod pedestal provides high stiffness with minimal weight. The antenna components are modular in design which provides options for motorization and tracking requirements. High performance molded cases are included.

The antenna is designed to meet international performance specifications for commercial or off-the-shelf military applications and is readily available in C, X, Ku, DBS and Ka band frequencies. Multiple feed and integration packages are available with a quick change / quick pack configuration. The integrated boom assembly with BUC and LNB packs in a single case for quick installation. Integrated feedbooms can be supplied which will allow a quick change from one frequency band to another.

- **Intelsat & Eutelsat Compliant (Using Appropriate Feed)**
- **Multi-Band C, X, Ku, DBS and Ka Band Frequencies**
- **Integrated Feedboom Assembly Option**
- **Compact Packaging – Packs in 4 Cases**
- **Excellent Stability in Wind**
- **Minimal Maintenance and High Reliability**
- **Less than 15 min Assembly Time**
- **Captive Hardware – No Tools for Assembly**
- **Fully Motorized Configuration Available**



<i>Electrical Specifications</i>	2 Port Cross-Pol C Band Extended Linear Feed		2 Port Cross-Pol C Band Std. Linear Feed		2 Port Cross-Pol C Band Circular Feed		2 Port X Band Circular Polarization		2 Port Cross-Pol Ku Band Linear / Mode Matched Feed	
	Rx	Tx	Rx	Tx	Rx	Tx	Rx	Tx	Rx	Tx
	Frequency (GHz)	3.40 - 4.20	5.85 - 6.725	3.625 - 4.2	5.85 - 6.425	3.625 - 4.2	5.85 - 6.425	7.25 - 7.75	7.9 - 8.4	10.95 - 12.75
Gain (Midband, dBi)	36.4	40.8	36.6	40.6	36.5	40.6	42.0	42.8	46.2	47.9
Noise Temperature (°K)										
10 deg El	51		45		55		68		53	
20 deg El	45		40		50		64		48	
Cross Pol										
On Axis	-30 dB	-30 dB	-30 dB	-30 dB	-20 dB	-27 dB	-30 dB	-30 dB	-35 dB	-35 dB
in 1 dB BW	-26 dB	-26 dB	-26 dB	-26 dB	-20 dB	-27 dB	-30 dB	-30 dB	-25 dB	-35 dB
Axial Ratio					1.6 dB	0.75 dB	0.5 dB	0.5 dB		
Sidelobe Compliances	Meets ITU 580 Beyond Mainbeam		Meets ITU 580 Beyond Mainbeam		Meets ITU 580 Beyond Mainbeam		MI-Std 188-164A		ITU, FCC Eutelsat	
VSWR	1.40:1	1.30:1	1.30:1	1.30:1	1.35:1	1.30:1	1.30:1	1.30:1	1.35:1	1.30:1
Isolation										
Tx/Rx	-85 dB	0 dBm input	-85 dB	0 dBm input	-85 dB	0 dBm input	-120 dB	0 dBm input	-85 dB	0 dBm input
Rx/Tx	0 dBm input	-35 dB	0 dBm input	-35 dB	0 dBm input	-35 dB	0 dBm input	-120 dB	0 dBm input	-30 dB

<i>Mechanical / Environmental Specifications</i>	
Reflector	2.0 meters (78.75 in) Carbon Fiber
Reflector Configuration	Parabolic Single Offset, 0.8 F/D (7 pieces)
Antenna Travel	
Azimuth	360° continuous with fine adjust
Elevation	5 - 90° of reflector bore sight
Polarization	± 90°
Antenna Packaging	
Case 1 - Backbeam & Legs	44.9" x 25.3" x 16.5" (110 lbs)
Case 2 - Az Hub, El Strut, Foot Pads	37.5" x 27.5" x 14.5" (98 lbs)
Case 3 & 4 - (7 piece reflector)	42" x 13" x 34.5" (85 lbs ea.)
Total Weight (less feed options)	378 lbs (172 kg)
Temperature	
Operational	-30 to 60°C (-22 to 140°F)
Survival	-40 to 70°C (-48 to 158°F)
Pointing Loss (operational winds)	3dB peak (Ku-band Rx)
Winds	
Operational	30 Gusting to 45 mph (40 kph G 72 kph) with ballast or anchors
Optional Wind Strut Accessory	45 mph (72 kph)
Survival	60 mph (96 kph) with tie downs / any position
Feedboom Mounted Integration	60 lbs (27.2 kg)
Rain	
Operational	2 in/h (5 cm/h)
Survival	4 in/h (10 cm/h)
Relative Humidity	0 - 100% (condensing)
Solar Radiation	360 btu/h/ft ² (1000 Kcal/h/m ²)
Radial Ice (survival)	1/2 in (12.7 mm)
Corrosive Atmosphere	As encountered in coastal and/or industrial areas

* Feed packaged separately dependent on options ordered
 ** Performance dependent on proper installation and ballast/anchors
 *** Dependent on position of weight. Consult Engineering for details
 Note: Specifications subject to change without notice.