

# 2031 Agilis

## 2.0 Meter Motorized Flyaway Antenna



- **Intelsat & Eutelsat Compliant (Using appropriate feed)**
- **Multi-Band C, X, Ku and Ka Band Frequencies**
- **Integrated Feedboom Assembly Option**
- **Compact Packaging**
- **Superior Stability in Wind**
- **Excellent Reliability**
- **Minimal Maintenance**
- **Less than 15 min Assembly Time**
- **Captive Hardware**

The Sat-Lite Technologies Model 2031 Agilis motorized carbon fiber flyaway antenna offers superior performance in a lightweight, portable package. This antenna features a 7 piece carbon fiber segmented reflector designed to provide high gain and low cross pol characteristics. The motorization package includes a ruggedized outdoor mounted controller with preconnectorized cables allowing for quick assembly and disassembly. The custom-designed elevation-over-azimuth tripod pedestal provides high stiffness with minimal weight. The antenna components are modular in design which also reduces assembly time and provides an improved packaging scheme requiring less time and effort to pack or unpack the antenna. The molded cases are included.

The antenna is designed to meet international performance specifications for commercial or off-the-shelf military applications and is readily available in C, X, Ku and Ka band frequencies. Multiple feed and integration configurations are available.



## TECHNICAL SPECIFICATIONS

| Electrical<br>Specifications | 2 Port Cross-Pol C Band       |              | 2 Port Cross-Pol C Band |                               | 2 Port Cross-Pol C Band |              | 2 Port X Band                 |             | 2 Port Cross-Pol Ku Band   |                   |
|------------------------------|-------------------------------|--------------|-------------------------|-------------------------------|-------------------------|--------------|-------------------------------|-------------|----------------------------|-------------------|
|                              | Extended Linear Feed          |              | Std. Linear Feed        |                               | Circular Feed           |              | Circular Polarization         |             | Linear / Mode Matched Feed |                   |
|                              | Rx                            | Tx           | Rx                      | Tx                            | Rx                      | Tx           | Rx                            | Tx          | Rx                         | Tx                |
| Frequency (GHz)              | 3.40 - 4.20                   | 5.85 - 6.725 | 3.625 - 4.2             | 5.85 - 6.425                  | 3.625 - 4.2             | 5.85 - 6.425 | 7.25 - 7.75                   | 7.9 - 8.4   | 10.95 - 12.75              | 13.75 - 14.5      |
| Gain (Midband, dBi)          | 36.4                          | 40.8         | 36.6                    | 40.6                          | 36.5                    | 40.6         | 42.0                          | 42.8        | 46.2                       | 47.9              |
| Noise Temperature (°K)       |                               |              |                         |                               |                         |              |                               |             |                            |                   |
| 10 deg E                     | 51                            |              | 45                      |                               | 55                      |              | 68                            |             | 53                         |                   |
| 20 deg E                     | 45                            |              | 40                      |                               | 50                      |              | 64                            |             | 48                         |                   |
| Cross Pol                    |                               |              |                         |                               |                         |              |                               |             |                            |                   |
| On Axis                      | -30 dB                        | -30 dB       | -30 dB                  | -30 dB                        | -20 dB                  | -27 dB       | -30 dB                        | -30 dB      | -35 dB                     | -35 dB            |
| in 1 dB BW                   | -26 dB                        | -26 dB       | -26 dB                  | -26 dB                        | -20 dB                  | -27 dB       | -30 dB                        | -30 dB      | -25 dB                     | -35 dB            |
| Axial Ratio                  |                               |              |                         |                               | 1.6 dB                  | 0.75 dB      | 0.5 dB                        | 0.5 dB      |                            |                   |
| Sidelobe Compliances         | Meets ITU 580 Beyond Mainbeam |              |                         | Meets ITU 580 Beyond Mainbeam |                         |              | Meets ITU 580 Beyond Mainbeam |             |                            | ITU, FCC Eutelsat |
| VSWR                         | 1.40:1                        | 1.30:1       | 1.30:1                  | 1.30:1                        | 1.35:1                  | 1.30:1       | 1.30:1                        | 1.30:1      | 1.35:1                     | 1.30:1            |
| Isolation                    |                               |              |                         |                               |                         |              |                               |             |                            |                   |
| Tx/Rx                        | -85 dB                        | 0 dBm input  | -85 dB                  | 0 dBm input                   | -85 dB                  | 0 dBm input  | -120 dB                       | 0 dBm input | -85 dB                     | 0 dBm input       |
| Rx/Tx                        | 0 dBm input                   | -35 dB       | 0 dBm input             | -35 dB                        | 0 dBm input             | -35 dB       | 0 dBm input                   | -120 dB     | 0 dBm input                | -30 dB            |

### Mechanical / Environmental Specifications

|   |  |
|---|--|
| Reflector   | 2.0 meters (78.75 in) Carbon Fiber                             |
| Reflector Configuration                                 | Parabolic Single Offset, 0.8 F/D (7 pieces)                    |
| Antenna Travel  |  |
| Azimuth   | +/- 180° continuous  |
| Elevation   | 5 - 90° of reflector bore sight                                |
| Polarization  | ± 90°  |
| Motorized Antenna Packaging (Tri-Band Configuration***) |  |
| Case 1 - Pedestal Legs / Backbeam                       | 44.9" x 25.3" x 16.5" , 92 lbs (42 Kg)                         |
| Case 2 - Az Hub / Foot Pads / El Actuator / CTLR        | 37.5" x 27.5" x 14.5" , 124 lbs (56 Kg)                        |
| Case 3 & 4 - (7 piece reflector)                        | 42" x 13" x 34.5", 72 lbs ea., (33 Kg ea.)                     |
| Integrated Feed Case with BUC (Per Band)                | (Depending on Feed and BUC)                                    |
| Total Weight (less feed options)                        | 360 lbs (164 Kg)   |
| Temperature   |  |
| Operational   | -20 to 60°C (-4 to 140°F)                                      |
| Survival  | -40 to 70°C (-48 to 158°F)                                     |
| Pointing Loss (operational winds)***                    | 2dB typical (Ku-band Rx)                                       |
| Winds   |  |
| Operational   | 30 Gusting to 45 mph (40 kph G 72 kph) with ballast or anchors |
| Survival  | 60 mph (96 kph) with tie downs / any position                  |
| Feedboom Mounted Integration****                        | 60 lbs typical (27.2 kg)                                       |
| Rain  |  |
| Operational   | 2 in/h (5 cm/h)  |
| Survival  | 4 in/h (10 cm/h)   |
| Relative Humidity                                       | 0 - 100% (condensing)  |
| Solar Radiation   | 360 btu/h/ft <sup>2</sup> (1000 Kcal/h/m <sup>2</sup> )        |
| Radial Ice (survival)                                   | 1/2 in (12.7 mm)   |
| Corrosive Atmosphere                                    | As encountered in coastal and/or industrial areas              |

\* Lower Axial Ratio Feeds Available.

\*\* For Ka Band applications, pedestal configuration and packaging not shown.

\*\*\* Performance dependent on proper installation and ballast/anchors

\*\*\*\* Dependent on position of weight. Consult Engineering for details

Note: Specifications subject to change without notice.