



DS-4 De-Ice Controller

Walton DS-4 Rain/Snow Sensor/Controller

The DS-4 Automatic local Control Unit operates by detecting temperature through a thermistor and precipitation using a moisture sensor. These signals are then supplied to the microcontroller, which will activate your de-icing system. The DS-4 Controller can be powered by either 110-120 VAC or 200-240 VAC 50/60 Hz power.

Features

- Automatic Activation Lowers De-icing Operational Costs
- Reliable Rain and Snow Detection
- Field Strap for 100-120/200-240 VAC Operation
- Replaceable Precipitation Sensor
- 16 Different Functions
- Easy Installation and Full Access to Electronics
- Adjustable Temperature Trigger Point
- Adjustable Delay Off Cycle
- Selectable Low Temperature Cutoff

[Request A Quote](#)

DP-7EX De-Ice Controller

Walton DP-7EX Remote Monitor/Control Unit



The DP-7EX is mounted on a 1.75" X 19" standard, single rack mount panel. The black powder finish assures high indicator visibility, even from a long distance. Termination of the cabling from the local unit is easily made through the rear mounted terminal blocks on the back of the unit. All connections to the unit are clearly marked on the rear of the panel to simplify installation. A de-pluggable terminal block for interface also makes swap-out a snap.

Control Leads going to the DS-4 Local Control/Sensor are optoisolated in order to improve noise immunity, reduce ground loop problems, and provide circuit protection. This also allows the DP-7EX to be mounted up to 1200 feet away from the Local (DS-4) Control/Sensor. Dry contact I/O for customer monitor and control equipment is also provided for monitoring the status of the deicing system along with allowing full remote Manual On activation, no matter what position the DP-7EX control Switch is in. A panel indicator will show a remote M&C Manual On command.

Features

- Inexpensive Assurance of Proper De-icing Operation
- Full Remote Control for Testing
- 100-120VAC Standard, 200-240 VAC Optional
- Controls can be located up to 1200 Feet from the Local Antenna De-ice Controls
- Stand or High Density Configurations Available



DS-4 Automatic Local Controller which is integrated into the Power Distribution Panel

The DP-7EX remote control/status display panels coupled with the DS-4 provides a low cost method to remotely monitor and control your De-icing System. The DP-7EX provides basic De-ice on Status for the de-icing system, along with Manual on, Automatic, and Standby control capabilities. The DP-7EX also allows monitoring thermal switches, on up to eight antenna points, to confirm that heat is being applied where required.